





SPECIFICATIONS

All-Mountain Trail
Small, Medium, Large
53.1lbs
YAMAHA Dual Twin
RockShox YARI RC 160mm Boost
RockShox Supreme Deluxe Select + 210x55 160mm travel
YAMAHA Multilocation 500Wh 36V Lithium Ion
YAMAHA exclusive PW-X2 Quad Sensor System with new AUTO, MTB and Push Assist modes
ISIS Spline. 170mm
36t 104BCD
Shimano XT
Shimano XT
Magura MT30 with 203mm Storm CL rotors. Front 4-Piston, Rear 4-Piston
Shimano XT 11s 11-46t
KMC e11 Turbo EPT
YAMAHA 27.5+ Alloy. Tubeless tape installed. 40mm inner rim width
Front and Rear Maxxis High Roller II 27.5x2.8"
Integrated tapered with 30mm steerer spacers
YAMAHA Alloy 4-bolt faceplate, 35.0 dia., 40mm length.
YAMAHA Alloy 30mm rise, 35.0 dia., 780mm wide
Locking Dual Core
Alloy 30.9 dia. dropper post. (S/M) 125mm travel, (L) 150mm travel.
Single-bolt. 35.0mm dia.
YAMAHA Anti-Slip with Hand Rail Tail

FEATURES

	Dual Twin frame design			
	160mm All Mountain Travel Front and Rear			
	27.5+ Tubeless Ready Wheelset			
	All-New PW-X2 with Quad Sensor System			
Rear hub speed sensor				
	Max torque: 80 Nm			
	Max cadence support: 170rpm			
	5 Manual Assist Modes: ECO, STANDARD, HIGH, MTB, EXPW			
Automatic Mode: ECO, STANDARD HIGH Internal cable/housing routing				
	Component manufacturer's warranty is supported by YAMAHA * Full details on warranty sheet			

FRAME GEOMETRY

	Small	Medium	Large
Top Tube	572	619	666
Reach	388	432	478
Stack	611	619	624
Standover Height	746	755	763
Head Tube Length	111	120	125
Head Tube Angle	66.3	66.3	66.3
Seat Tube Length	390	400	410
Seat Tube Angle	70.3	70.3	70.3
BB Drop	19	19	19
Wheelbase	1157	1205	1253
Rear Center	469	469	469